

SINCE 1978



LEADING LIGHT

# Product Datasheet

vkleadinglight.gr

Jade

## VK/02291/GR/WW/53


Sand Green. 2700K. 1W. 182lm. AC220-240V, DC24V. LED Bridgelux. 50.000hrs. Diffuse Light. Dimmable No. -20°C→ 45°C. Aluminum + Acrylic. Outdoor ground. CRI>90. 53.4cm. Included Spike & base. IP65




IP65



### Dimensions



### Gallery




MODEL	HEIGHT	DIAMETER	POWER	BEAM ANGLE	IP
VK/02291/GR/WW/53	53.4cm	65cm	1W	120°	IP65
VK/02291/GR/WW/54	45cm	65cm	1W	120°	IP65
VK/02291/GR/WW/55	35cm	65cm	1W	120°	IP65
VK/02291/GR/WW/56	25cm	65cm	1W	120°	IP65
VK/02291/GR/WW/57	15cm	65cm	1W	120°	IP65

### Downloads




VK Leading Light

Since 1978

Technical Specifications	
Kelvin	2700K
Power	1W
Voltage	AC220-240V, DC24V
Fitting	Outdoor ground
Type	Light
Safety class	N3
Light source	Bridgelux
IP Rating	<b>IP65</b>
CRI	CRI>90
Dimmable	
Lifetime	50.000hrs
Working temperature	-20°C-45°C
PAGE	376 New Products 2026
NICKNAME	Jade

Physical Specifications	
Family	Jade
Color	Sand green
Material	Aluminum + acrylic
Width	ø6cm
Length	ø6cm
Height	53.4cm

Illumination Data	
Lumen	182lm
Lighting direction	

Packing Info	
Pcs/carton	20pcs

Certification & Warranty

Guarantee	3 years
-----------	---------

Energy Label

The image shows an energy label for a VK Leading Light. At the top left is the European Union flag and the word "ENERGY" with a lightning bolt icon. Below this, the text "VK LEADING LIGHT" and "VK/02291/GR/WW/53" is displayed. The main part of the label is a vertical scale of seven colored arrows pointing to the right, labeled A through G. The arrow for 'F' is highlighted with a black arrow pointing to it from the right. Below the scale, the energy consumption is listed as "2 kWh/1000h". To the right of this text is a QR code and the date "2019/2015".