


## General info

### Indoor - Suspensions

|              |                    |
|--------------|--------------------|
| Ean          | 8021696366425      |
| Item         | DORICA SP1 D45 BLU |
| Installation | Suspensions        |
| Warranty     | 5 years            |
| Gross weight | 3.1 kg             |
| Volume       | 0.008869 m³        |

## Technical info

|                       |                                                                                |
|-----------------------|--------------------------------------------------------------------------------|
| Net weight            | 2.3 kg                                                                         |
| Insulation class      | II                                                                             |
| Protection index      | IP20                                                                           |
| Compliance            | CE                                                                             |
| Operating temperature | 0° ~ +40 °C                                                                    |
| Dimmer                | 1, DALI / Push                                                                 |
| Power output          | 220-240 V AC 50/60 Hz                                                          |
| Power supply          | In-built, included<br>Replaceable (by qualified operators only),<br>electronic |

## Source info

|                        |                       |
|------------------------|-----------------------|
| Integrated source      | Integrated LED module |
| Repleaceable source    | No                    |
| Power                  | LED 35 W              |
| Emission               | Direct                |
| Max consupcion         | max 35 W              |
| Features LED           | LED SMD BRIDGELUX     |
| CCT LED                | 3000 K                |
| Duration LED (t. 25°C) | 50000 h               |
| CRI                    | > 90                  |
| SDCM                   | 3                     |
| Light beam flux        | 4000 lm               |
| Useful light flux      | 1120 lm               |
| Photobiological risk   | 1                     |
| Standby power          | < 0.50 W              |