

SINCE 1978



LEADING LIGHT

Product Datasheet

vkleadinglight.gr

Candle

VK/05083/EI/W

Led lamp, E14, 6W, 3000K, 540lm, candle, plastic, white



IP20   

Dimensions	Gallery	Downloads																																																																																																																								
	Led Lamp - E14-E27 Candle Plastic MODEL7 <table><tr><th>Model</th><th>Power (W)</th><th>Color Temp (K)</th><th>Beam Angle (°)</th><th>Light Flux (lm)</th><th>Life Span (h)</th></tr><tr><td>MODEL7-001</td><td>6</td><td>3000</td><td>270</td><td>540</td><td>25000</td></tr><tr><td>MODEL7-002</td><td>6</td><td>4000</td><td>270</td><td>540</td><td>25000</td></tr><tr><td>MODEL7-003</td><td>6</td><td>5000</td><td>270</td><td>540</td><td>25000</td></tr></table> MODEL7-004 <table><tr><th>Model</th><th>Power (W)</th><th>Color Temp (K)</th><th>Beam Angle (°)</th><th>Light Flux (lm)</th><th>Life Span (h)</th></tr><tr><td>MODEL7-004</td><td>6</td><td>3000</td><td>270</td><td>540</td><td>25000</td></tr><tr><td>MODEL7-005</td><td>6</td><td>4000</td><td>270</td><td>540</td><td>25000</td></tr><tr><td>MODEL7-006</td><td>6</td><td>5000</td><td>270</td><td>540</td><td>25000</td></tr></table> MODEL7-007 <table><tr><th>Model</th><th>Power (W)</th><th>Color Temp (K)</th><th>Beam Angle (°)</th><th>Light Flux (lm)</th><th>Life Span (h)</th></tr><tr><td>MODEL7-007</td><td>6</td><td>3000</td><td>270</td><td>540</td><td>25000</td></tr><tr><td>MODEL7-008</td><td>6</td><td>4000</td><td>270</td><td>540</td><td>25000</td></tr><tr><td>MODEL7-009</td><td>6</td><td>5000</td><td>270</td><td>540</td><td>25000</td></tr></table> MODEL7-010 <table><tr><th>Model</th><th>Power (W)</th><th>Color Temp (K)</th><th>Beam Angle (°)</th><th>Light Flux (lm)</th><th>Life Span (h)</th></tr><tr><td>MODEL7-010</td><td>6</td><td>3000</td><td>270</td><td>540</td><td>25000</td></tr><tr><td>MODEL7-011</td><td>6</td><td>4000</td><td>270</td><td>540</td><td>25000</td></tr><tr><td>MODEL7-012</td><td>6</td><td>5000</td><td>270</td><td>540</td><td>25000</td></tr></table> MODEL8 <table><tr><th>Model</th><th>Power (W)</th><th>Color Temp (K)</th><th>Beam Angle (°)</th><th>Light Flux (lm)</th><th>Life Span (h)</th></tr><tr><td>MODEL8-001</td><td>6</td><td>3000</td><td>270</td><td>540</td><td>25000</td></tr><tr><td>MODEL8-002</td><td>6</td><td>4000</td><td>270</td><td>540</td><td>25000</td></tr><tr><td>MODEL8-003</td><td>6</td><td>5000</td><td>270</td><td>540</td><td>25000</td></tr></table>	Model	Power (W)	Color Temp (K)	Beam Angle (°)	Light Flux (lm)	Life Span (h)	MODEL7-001	6	3000	270	540	25000	MODEL7-002	6	4000	270	540	25000	MODEL7-003	6	5000	270	540	25000	Model	Power (W)	Color Temp (K)	Beam Angle (°)	Light Flux (lm)	Life Span (h)	MODEL7-004	6	3000	270	540	25000	MODEL7-005	6	4000	270	540	25000	MODEL7-006	6	5000	270	540	25000	Model	Power (W)	Color Temp (K)	Beam Angle (°)	Light Flux (lm)	Life Span (h)	MODEL7-007	6	3000	270	540	25000	MODEL7-008	6	4000	270	540	25000	MODEL7-009	6	5000	270	540	25000	Model	Power (W)	Color Temp (K)	Beam Angle (°)	Light Flux (lm)	Life Span (h)	MODEL7-010	6	3000	270	540	25000	MODEL7-011	6	4000	270	540	25000	MODEL7-012	6	5000	270	540	25000	Model	Power (W)	Color Temp (K)	Beam Angle (°)	Light Flux (lm)	Life Span (h)	MODEL8-001	6	3000	270	540	25000	MODEL8-002	6	4000	270	540	25000	MODEL8-003	6	5000	270	540	25000	 
Model	Power (W)	Color Temp (K)	Beam Angle (°)	Light Flux (lm)	Life Span (h)																																																																																																																					
MODEL7-001	6	3000	270	540	25000																																																																																																																					
MODEL7-002	6	4000	270	540	25000																																																																																																																					
MODEL7-003	6	5000	270	540	25000																																																																																																																					
Model	Power (W)	Color Temp (K)	Beam Angle (°)	Light Flux (lm)	Life Span (h)																																																																																																																					
MODEL7-004	6	3000	270	540	25000																																																																																																																					
MODEL7-005	6	4000	270	540	25000																																																																																																																					
MODEL7-006	6	5000	270	540	25000																																																																																																																					
Model	Power (W)	Color Temp (K)	Beam Angle (°)	Light Flux (lm)	Life Span (h)																																																																																																																					
MODEL7-007	6	3000	270	540	25000																																																																																																																					
MODEL7-008	6	4000	270	540	25000																																																																																																																					
MODEL7-009	6	5000	270	540	25000																																																																																																																					
Model	Power (W)	Color Temp (K)	Beam Angle (°)	Light Flux (lm)	Life Span (h)																																																																																																																					
MODEL7-010	6	3000	270	540	25000																																																																																																																					
MODEL7-011	6	4000	270	540	25000																																																																																																																					
MODEL7-012	6	5000	270	540	25000																																																																																																																					
Model	Power (W)	Color Temp (K)	Beam Angle (°)	Light Flux (lm)	Life Span (h)																																																																																																																					
MODEL8-001	6	3000	270	540	25000																																																																																																																					
MODEL8-002	6	4000	270	540	25000																																																																																																																					
MODEL8-003	6	5000	270	540	25000																																																																																																																					

Technical Specifications	
Kelvin	3000K
Power	6W
Voltage	180-250V
Lampholder	E14
Fitting	Ceiling
Type	Led lamps E14
Light source	SMD 2835
IP Rating	IP20
CRI	Ra>80
Dimmable	
Lifetime	25.000 hrs
Clicks	100K clks
Working temperature	-20°C - 40°C
PAGE	52 Electrical

Physical Specifications	
Color	White
Material	Plastic, Alu
Width	37mm
Height	98mm

Illumination Data	
Lumen	540lm
Beam angle	180°

Packing Info	
Pcs/carton	100pcs

Certification & Warranty	
Guarantee	2 years

Energy Label



VK LEADING LIGHT
VK/05083/EI/W

A

B

C

D

E

F

G

G

6

kWh/1000h



2019/2015