

SINCE 1978



LEADING LIGHT

Product Datasheet

vkleadinglight.gr

Smol

VK/04436/B/W


Recessed ceiling light led, 1W, 3000K, 65lm, 24°, CRI>90, IP20, ø2.3cm, black



IP20



Dimensions



Gallery



Recessed Dark downlights Led

Smol

Model	Power (W)	Beam angle (°)	Color temperature (K)	Light output (lm)	IP	Material
VK/04436/B/W	1	24	3000	65	IP20	Aluminum
VK/04436/B/W	1	24	4000	65	IP20	Aluminum
VK/04436/B/W	1	24	5000	65	IP20	Aluminum
VK/04436/B/W	1	24	6000	65	IP20	Aluminum

12

Downloads



Technical Specifications	
Kelvin	3000K
Power	1W
Voltage	100-260V
Fitting	Recessed dark ceiling
Type	Downlight LED
Safety class	
Light source	OSRAM SMD
IP Rating	IP20
CRI	CRI>90
Dimmable	
Lifetime	20.000hrs
Driver	Built-in DC 2-4V 300mA
Working temperature	< 45°C
PAGE	212 Technical 2024
NICKNAME	Smol

Physical Specifications	
Recessed ceiling	Yes
Color	Black matt
Material	Aluminium
Width	ø2.3cm
Length	ø2.3cm
Height	3.5cm
Net weight of product (kg)	0.03
Gross weight with inner box (kg)	0.05
Gross weight with master box (kg)	2.80
Cut out	ø2cm H3.5cm (the cut hole also fits the light driver)

Illumination Data	
Lumen	65lm
Beam angle	24°
Lighting direction	
Dark light	Yes

Packing Info	
Pcs/carton	50pcs

Certification & Warranty	
Guarantee	3 years

Energy Label



VK LEADING LIGHT
VK/04436/B/W

A

B

C

D

E

F

G

1

kWh/1000h



2019/2015

F