

SINCE 1978



LEADING LIGHT

Product Datasheet

vkleadinglight.gr


VK/04149/W/W/24

Uta

Recessed adjustable spot led, 15W, 3000K, 1.350lm, 24°, IP65, ø18x12cm, white



IP65    

Dimensions	Gallery	Downloads																																																																		
	 LED Downlights waterproof IP65 Uta  <table><thead><tr><th>Model</th><th>Power</th><th>Beam angle</th><th>Color temperature</th><th>Light output</th><th>Dimensions</th></tr></thead><tbody><tr><td>VK/04149/W/W/24</td><td>15W</td><td>24°</td><td>3000K</td><td>1.350lm</td><td>ø18x12cm</td></tr><tr><td>VK/04149/W/W/24</td><td>15W</td><td>24°</td><td>3000K</td><td>1.350lm</td><td>ø18x12cm</td></tr><tr><td>VK/04149/W/W/24</td><td>15W</td><td>24°</td><td>3000K</td><td>1.350lm</td><td>ø18x12cm</td></tr><tr><td>VK/04149/W/W/24</td><td>15W</td><td>24°</td><td>3000K</td><td>1.350lm</td><td>ø18x12cm</td></tr><tr><td>VK/04149/W/W/24</td><td>15W</td><td>24°</td><td>3000K</td><td>1.350lm</td><td>ø18x12cm</td></tr><tr><td>VK/04149/W/W/24</td><td>15W</td><td>24°</td><td>3000K</td><td>1.350lm</td><td>ø18x12cm</td></tr><tr><td>VK/04149/W/W/24</td><td>15W</td><td>24°</td><td>3000K</td><td>1.350lm</td><td>ø18x12cm</td></tr><tr><td>VK/04149/W/W/24</td><td>15W</td><td>24°</td><td>3000K</td><td>1.350lm</td><td>ø18x12cm</td></tr><tr><td>VK/04149/W/W/24</td><td>15W</td><td>24°</td><td>3000K</td><td>1.350lm</td><td>ø18x12cm</td></tr><tr><td>VK/04149/W/W/24</td><td>15W</td><td>24°</td><td>3000K</td><td>1.350lm</td><td>ø18x12cm</td></tr></tbody></table> Notes: - In case of 24° beam angle, the light output is 1.350lm. - Beam angle 24° is the standard. - Color temperature 3000K is the standard. 	Model	Power	Beam angle	Color temperature	Light output	Dimensions	VK/04149/W/W/24	15W	24°	3000K	1.350lm	ø18x12cm	VK/04149/W/W/24	15W	24°	3000K	1.350lm	ø18x12cm	VK/04149/W/W/24	15W	24°	3000K	1.350lm	ø18x12cm	VK/04149/W/W/24	15W	24°	3000K	1.350lm	ø18x12cm	VK/04149/W/W/24	15W	24°	3000K	1.350lm	ø18x12cm	VK/04149/W/W/24	15W	24°	3000K	1.350lm	ø18x12cm	VK/04149/W/W/24	15W	24°	3000K	1.350lm	ø18x12cm	VK/04149/W/W/24	15W	24°	3000K	1.350lm	ø18x12cm	VK/04149/W/W/24	15W	24°	3000K	1.350lm	ø18x12cm	VK/04149/W/W/24	15W	24°	3000K	1.350lm	ø18x12cm	
Model	Power	Beam angle	Color temperature	Light output	Dimensions																																																															
VK/04149/W/W/24	15W	24°	3000K	1.350lm	ø18x12cm																																																															
VK/04149/W/W/24	15W	24°	3000K	1.350lm	ø18x12cm																																																															
VK/04149/W/W/24	15W	24°	3000K	1.350lm	ø18x12cm																																																															
VK/04149/W/W/24	15W	24°	3000K	1.350lm	ø18x12cm																																																															
VK/04149/W/W/24	15W	24°	3000K	1.350lm	ø18x12cm																																																															
VK/04149/W/W/24	15W	24°	3000K	1.350lm	ø18x12cm																																																															
VK/04149/W/W/24	15W	24°	3000K	1.350lm	ø18x12cm																																																															
VK/04149/W/W/24	15W	24°	3000K	1.350lm	ø18x12cm																																																															
VK/04149/W/W/24	15W	24°	3000K	1.350lm	ø18x12cm																																																															
VK/04149/W/W/24	15W	24°	3000K	1.350lm	ø18x12cm																																																															

Technical Specifications	
Kelvin	3000K
Power	15W
Voltage	85-265V
Fitting	Recessed ceiling
Type	Waterproof Downlight LED
Safety class	
Light source	Toyonia
IP Rating	IP65
CRI	CRI>90
Dimmable	
Lifetime	50.000hrs
Clicks	20.000clicks
Working temperature	-20°C - 45°C
PAGE	248 Technical 2024
NICKNAME	Uta

Physical Specifications	
Adjustable	
Recessed ceiling	Yes
Color	White
Material	Aluminium, Plastic
Width	ø18cm
Length	ø18cm
Height	12cm
Cut out	ø15cm depth 12cm

Illumination Data	
Lumen	1.350lm
Beam angle	24°
Lighting direction	

Packing Info	
Pcs/carton	16pcs

Certification & Warranty	
Guarantee	2 years